



300A GRAFFITI REMOVER

Introduction: Sure Seal® 300A Graffiti Remover is the “next generation” of environmentally friendly Graffiti Removers. 300A Graffiti Remover is based on a blend of low-odour solvents and emulsifying agents for removal of graffiti. It contains a unique catalyst which dramatically reduces stripping times. Developed specifically for the removal of graffiti from all substrates; including brickwork, concrete, metal, glass and timber surfaces. Removes residue left from spray cans, felt pen based paints and inks.

Summary of the Features and Benefits:

- ✓ Low odour/no unpleasant solvent fumes
- ✓ Fast Acting/Easy to apply – removes all types of graffiti in up to 2-3 minutes
- ✓ Easy Rinsing – pressure washer or low pressure hand-held spray pump
- ✓ Multi-Uses – works on numerous surfaces, including concrete, brickworks, metal, glass and timber surfaces

A safer method of removing graffiti	✓ Non Hazardous	✓ Non-Toxic	✓ Non- Irritant
	✓ User Friendly	✓ Readily Biodegradable	✓ Non Flammable
	✓ VOC Compliant	✓ Low odour	

Mixing: Ready-to-use product. Use as is and do not dilute. Shake container before use.

Application Methods: Surface must be dry before application. Always test product in an inconspicuous area for suitability. Apply to the surface and agitate using a brush or broom. Allow up to 3 minutes contact time, then rinse off with water using a pressure washer, or where use of a pressure washer to rinse off is not practical, use a low pressure hand-held spray pump.

Coverage: One litre will cover approximately 15-20 sq. metres depending upon the porosity of the surface to be treated and method of application.

Cleaning of Application Equipment: Rinse brush or broom with warm or cold water.

Quantities: Supplied in 20 litre drums.



**Sure Seal® Solutions
Australia Pty Ltd.**

ABN 94 128 678 035

P.O. Box 3686, Burleigh Town QLD 4220 • Ph: 07 5568 7037 • info@sssu.com.au • www.suresealcommercial.com.au



300A GRAFFITI REMOVER

Technical Data:

Appearance: Clear, pale amber liquid

Odour: Mild

Flash Point: >65°C

Pre-Test: As masonry materials and graffiti paints vary significantly, a test should be conducted prior to application to find out the suitability of the product for the intended purpose.

Application Methods: Ensure surface is dry then apply Sure Seal 300A Graffiti Remover directly onto the affected area with a paint sprayer or soft brush. For large areas apply with a soft broom or sprayer. Agitate the area with a brush and allow 2-3 minutes or longer if necessary to allow product to penetrate the graffiti. Rinse with pressure washer or low pressure garden water spray pump or hose.

Re-apply the product on any stubborn areas until all graffiti has been removed. Take care when applying to painted surfaces. Reduce the dwell time on painted surfaces. Avoid rubbing area with rags or abrasive materials. Test on a small inconspicuous area to check the compatibility before use.

Clean Up: Clean up all equipment in water.

Coverage: One litre will cover approximately 15-20 sq. metres depending upon the porosity of the surface to be treated and method of application.

First Aid:

Ingestion: If swallowed, DO NOT induce vomiting. Give a glass of water to drink and call a physician immediately.

Eye Contact: If material is splashed into eyes, flush immediately with plenty of water for 15 minutes, ensuring eye lids are held open. If irritation persists transport to hospital or doctor.

Skin Contact: Remove contaminated clothing and wash skin thoroughly with soap and water. If irritation persists transport to hospital or doctor.

Inhalation: If inhaled, move victim to fresh air. Apply resuscitation if victim is not breathing. Seek medical assistance.

Protective Clothing: Wear appropriate chemical resistant protective clothing including appropriate PVC or rubber gloves and goggles to protect eyes. See MSDS for further information.

Handling & Storage: Store in a cool place and out of direct sunlight and from sources of heat or ignition or from oxidizing agents. Keep containers closed when not using the product. Store in original packages as approved by the manufacturer. Dispose of in accordance with appropriate State authority. Keep out of reach of children.

Shipping Information: This product has no UN classification. This product is not a Scheduled S5 Poison. Not classified as a Dangerous Good, according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (6th Edition).

See Material Safety Data Sheet for complete safety and handling instructions

Note: Consult the Material Safety Data Sheet for further safety details. It is recommended to test the product on a small inconspicuous area to determine its efficacy or unexpected results.

**Sure Seal® Solutions
Australia Pty Ltd.**

ABN 94 128 678 035

P.O. Box 3686, Burleigh Town QLD 4220 • Ph: 07 5568 7037 • info@sssu.com.au • www.suresealcommercial.com.au