



GRAFFITI REMOVER

AEROSOL 500 g



Sure Seal® GRAFFITI REMOVER is a new and specially formulated blend of solvents and biodegradable surfactants designed and developed to remove graffiti from brick, stone, metals, concrete, glass, tiles, timber, reflective signs and many other surfaces.

FEATURES AND BENEFITS:

- ✓ Fast Acting & Easy to apply
- ✓ Removes all types of graffiti in minutes
- ✓ Removes paint, inks, markers, grease, tar, tyre marks and more!
- ✓ Works on all surfaces including concrete, brick, metal, glass and timber
- ✓ Non Toxic
- ✓ Non Hazardous
- ✓ Readily Biodegradable
- ✓ Non Flammable
- ✓ Low Odour
- ✓ No unpleasant solvent fumes

Now in a large 500gm Aerosol can. Our unique nitrogen gas propellant technology is non-flammable, non-hazardous, non-toxic and totally safe to use.

- Removes spray paint
- Removes permanent marker
- Removes enamel paint
- Removes shadowing
- Removes all types of inks
- Removes grease, tar & dirt



**Sure Seal® Sealants
Australia Pty Ltd.**

ABN 37 609 038 575





As graffiti paints and substrates vary significantly a test should be conducted prior to application to find out the suitability of the product for the intended purpose. **Sure Seal® GRAFFITI REMOVER** is ready to use as is. Do not dilute.

APPLICATION:

1. Ensure surface is dry.
2. Hold can upright approximately 15-20cm from the surface, aim nozzle and spray directly onto the affected area.
3. Agitate the area with a brush and allow 1-2 minutes, or longer if necessary, to allow product to penetrate the graffiti.
4. On vertical hard surfaces, Graffiti Remover can be sprayed directly onto a clean cloth, then simply wipe the graffiti off!
5. Rinse with pressure washer or low pressure garden sprayer, hose or damp cloth.
6. Re-apply the product on any stubborn areas until all graffiti has been removed.
7. Take care when applying to painted surfaces. Reduce the dwell time and avoid rubbing with rags or abrasive materials on painted surfaces.
8. Test on a small inconspicuous area to check the compatibility before use.

CLEAN UP: Clean up all equipment in water.

BEWARE: Intentional misuse by deliberately concentrating or inhaling contents can be harmful.

CAUTION: PRESSURISED DISPENSER. PROTECT FROM SUNLIGHT AND DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50°C. DO NOT PIERCE OR BURN EVEN AFTER USE. DO NOT SPRAY ON A NAKED FLAME OR ANY INCANDESCENT MATERIAL. KEEP AWAY FROM SOURCES OF IGNITION. NO SMOKING.

FIRST AID: For advice contact a Poisons Information Centre. Phone Australia 131 126 New Zealand 0800 764 766 or a doctor. If swallowed DO NOT induce vomiting.

PROPELLANT: Nitrogen (A safe, non-toxic and non-flammable gas) Nitrogen is 78% of the air we breathe.

KEEP OUT OF REACH OF CHILDREN.
Refer to Safety Data Sheet for full technical and safety details



Disclaimer:
The information given in this data sheet is based on many years of experience and is correct to the best of our knowledge. As the storage, handling and application of this material is beyond our control; we can only be responsible for the quality of our product at the time of dispatch. We reserve the right to alter certain product parameters within the spectrum of properties in order to keep abreast of technical advances. It is the responsibility of the end user to determine the suitability of this material for any particular application

**Sure Seal® Sealants
Australia Pty Ltd.**

ABN 37 609 038 575