



SHADOW BUSTER GRAFFITI REMOVER GEL



Sure Seal® Shadow Buster Graffiti Remover is a unique gel formulation developed specifically to remove graffiti and shadowing from all types of surfaces including, but not limited to, brickwork, concrete, metal, glass, timber, signs, perspex and painted surfaces. Removes residue left from spray cans, felt pen based paints and inks.

BENEFITS & CHARACTERISTICS:

- No unpleasant solvent fumes
- Less product waste no runoff
- Applied to a concentrated area of graffiti or shadowing, draws out stubborn graffiti or shadowing from the surface for easy removal.
- Removes graffiti and/or shadowing in minutes
- Works on numerous surfaces

FEATURES:

- Low Odour
- Acts as a "Poultice"
- Easy Rinsing
- Gel Formulation
- Fast Acting/Easy to Apply
- Multi-Uses

A safer method of removing graffiti:

- Non Hazardous
- User Friendly
- VOC Compliant
- Non Flammable
- Non-Toxic
- Readily Biodegradable
- Low odour
- Non- Irritant



Quantities:
Supplied in 20 litre drums.

**Sure Seal® Sealants
Australia Pty Ltd.**

ABN 37 609 038 575





Mixing: Ready-to-use product. Use as is and do not dilute. Shake container before use.

Pre-Test: As masonry materials and graffiti paints vary significantly, a test should be conducted in an inconspicuous area prior to application to find out the suitability of the product for the intended purpose.

Application Method: Ensure surface is dry then apply Sure Seal Graffiti Shadow Buster directly onto the affected area with a soft brush or broom. Allow 2-3 minutes dwell time or longer if necessary to allow product to penetrate the graffiti. Rinse with pressure washer or low pressure garden water spray pump or hose. If shadowing of the graffiti appears once the surface is dry then re-apply the product using the above method only this time agitate the remover into the surface using a stiff bristle brush to drive the remover into the pores of the substrate, allow 2-3 minutes dwell time and rinse off again. Take care when applying to painted surfaces. Reduce the dwell time on painted surfaces. Avoid rubbing area with rags or abrasive materials.

Coverage: One litre will cover approximately 15-20 sq. metres depending upon the porosity of the surface to be treated and method of application.

Clean Up: Clean up all equipment in water.

Technical Data:

Appearance: Clear, pale amber liquid gel

Odour: Mild

Flash Point: >65°C

Disclaimer:

The information given in this data sheet is based on many years of experience and is correct to the best of our knowledge. As the storage, handling and application of this material is beyond our control, we can only be responsible for the quality of our product at the time of dispatch. We reserve the right to alter certain product parameters within the spectrum of properties in order to keep abreast of technical advances. It is the responsibility of the end user to determine the suitability of this material for any particular application

First Aid: Ingestion: If swallowed, DO NOT induce vomiting. Give a glass of water to drink and call a physician immediately.

Eye Contact: If material is splashed into eyes, flush immediately with plenty of water for 15 minutes, ensuring eye lids are held open. If irritation persists transport to hospital or doctor.

Skin Contact: Remove contaminated clothing and wash skin thoroughly with soap and water. If irritation persists transport to hospital or doctor.

Inhalation: If inhaled, move victim to fresh air. Apply resuscitation if victim is not breathing. Seek medical assistance.

Handling & Storage: Store in a cool place and out of direct sunlight and from sources of heat or ignition or from oxidizing agents. Keep containers closed when not using the product. Store in original packages as approved by the manufacturer. Dispose of in accordance with appropriate State authority. Keep out of reach of children.

Shipping Information: This product has no UN classification. This product is not a Scheduled S5 Poison. Not classified as a Dangerous Good, according to the Australian Code for the Transport of Dangerous Goods by Road and Rail (6th Edition).

See Safety Data Sheet for complete safety and handling instructions.



**Sure Seal® Sealants
Australia Pty Ltd.**

ABN 37 609 038 575