



TIMBER SEALER

Sure Seal® Timber Sealer is a high performance penetrating sealer developed to provide long lasting protection for timber surfaces. It is quick drying and easy to apply.

The deep penetrating formula leaves a clear, natural, hydrophobic finish for both raw and stained timber to protect them from water and oil based staining as well as leaching.

Sure Seal® Timber Sealer protection is durable, invisible, stain resistant and does not change the original finish or appearance of the timber. Utilizing exclusive resins and powerful U.V. screens, this formula provides superior protection from the damaging effects of extreme temperatures, humidity, mould, mildew, algae, rain, snow, and the sun's harmful rays. It will not flake or peel off the treated surface and still allows the timber to breathe.

KEY FEATURES

Sure Seal® Timber Sealer penetrates deeply... sealing and protecting timber from the most severe effects of Mother Nature. It is ideal for protecting timber surfaces including decks and indoor and outdoor furniture with unsurpassed results. Even previously stained or sealed timber will benefit from its superior protection. It is a cost effective and user friendly solution for preserving and extending the life of timber.

BENEFITS & CHARACTERISTICS:

- Australian Made
- Quick Drying & Easy To Apply
- Oil & Stain Resistant
- Invisible Protection
- Long Life – Lasts Up To 5 Years
- For Raw & Stained Timber
- Can be Used On Indoor & Outdoor Furniture & Decking etc.
- Preserves & Extends The Life Of The Furniture
- Blocks moisture penetration that causes mould & mildew
- Will not change the appearance of the surface
- Allows treated surface to breathe
- Resists UV degradation



Available in 300 gm Aerosol & 1 Litre containers.



**Sure Seal® Sealants
Australia Pty Ltd.**

ABN 37 609 038 575



TECHNICAL INFORMATION

Description: **Sure Seal® Timber Sealer** is a deep penetrating, natural finish sealer which assists in the prevention of oil and water-based staining on teak and other natural timbers.

Aerosol Directions for Application

Hold aerosol can approximately 15-20 cm away from desired surface, press spray button and apply a light even coat over the surface to be treated using a sweeping motion, overlapping sprayed areas for best coverage. For optimum protection, apply 2 coats allowing 20 minutes between coats. Allow sealer to cure at least 2-3 hours.

Liquid Directions for Application

Apply **Sure Seal® Timber Sealer** with a paint brush, flat lambs-wool applicator, pump or airless sprayer. Apply one coat with smooth even strokes, lightly coating the surface being treated. For optimum protection, apply 2 coats allowing 20 minutes between coats and allow sealer to cure at least 2-3 hours. If necessary, buff off any excess residue before the second coat is dry.

Maintenance

To clean treated areas, simply use water and mild detergent or any neutral (non-acidic) cleaner. Do not use harsh cleaning agents such as abrasive powders, ammonia, acids, bleach or abrasive scrubbing pads.

Coverage Sure Seal®

300 gm Aerosol seals approximately up to 18 m² depending on the material to be sealed and how it's applied. One litre will cover approximately up to 20-40m² depending upon the material to be treated and method of application.

Note Consult the Safety Data Sheet for full technical and safety details. It is recommended to test the product first on a small inconspicuous area to determine its efficacy or unexpected results.

Disclaimer:

The information given in this data sheet is based on many years of experience and is correct to the best of our knowledge. As the storage, handling and application of this material is beyond our control; we can only be responsible for the quality of our product at the time of dispatch. We reserve the right to alter certain product parameters within the spectrum of properties in order to keep abreast of technical advances. It is the responsibility of the end user to determine the suitability of this material for any particular application



**Sure Seal® Sealants
Australia Pty Ltd.**

ABN 37 609 038 575